

12,000 BTU/H

CEP-121C



Specifications

Cooling Capacity BTUH	12,000
SACC BTUH	6,500
Approx. Sq. Ft. Cooling	350-400
EER	9.04
Refrigerant	R-410A
Power Supply	115V 60Hz
Humidity Removal Pts/Hr.	4.81
Fan Only	Yes
Fan Speeds Cool/Fan	3/3
Air Delivery Max. CFM	210
Amps Cooling	11.8
dB Level (hi/low)	55/52/51
Maximum Fuse Size	15A
Power Cord	15A Parallel NEMA 5-15P
Window Mounting Kit	Yes
Remote Control	Yes
Shipping Weight (lbs.)	53.9
Dimensions (in.) H	12.79
W	17.32
D	27.36

Features

- Cool a room without any special wiring, and move the unit from room to room as needed
- Ideal wherever temporary cooling is needed or where a window A/C isn't an option
- Built-in condensate disposal
- 60" single hose for fast installation
- Automatic louver swing
- Washable filter is easily accessed
- 24-hour timer for better energy control

PORTABLE AIR CONDITIONER



Square Feet to be Conditioned	Capacity Needed (BTUH)
100 - 150	8,000
150 - 250	
250 - 300	
300 - 350	10,000
350 - 400	
400 - 450	
450 - 550	12,000



COOL



DEHUMIDIFY



FAN



1 Garantie limitée de 1 an
Year Limited Warranty
 Garantía limitada de un año

SOME LIMITATIONS APPLY.
 SEE PRINTED WARRANTY FOR DETAILS.
 Certaines restrictions s'appliquent, voir garantie imprimée pour plus de détails.
 Se aplican algunas limitaciones, consulte el documento impreso de la garantía para obtener detalles.