

8,000 BTU/H

CEP81C



Specifications

Cooling Capacity BTUH	8,000	
SACC BTUH	5,300	
Approx. Sq. Ft. Cooling	300-350	
EER	8.43	
Refrigerant	R-410A	
Power Supply	115V 60Hz	
Humidity Removal Pts./Hr.	3.38	
Fan Only	Yes	
Fan Speeds Cool/Fan	3/3	
Air Delivery Max. CFM	220	
Amps Cooling	12.0	
dB Level (hi/low)	54/52	
Maximum Fuse Size	15A	
Power Cord	15A Parallel NEMA 5-15P	
Window Mounting Kit	Yes	
Remote Control	Yes	
Shipping Weight (lbs.)	50.6	
Dimensions (in.)	H	26.38
	W	12.6
	D	12.6

PORTABLE AIR CONDITIONER



Features

- Cool a room without any special wiring, and move the unit from room to room as needed
- Ideal wherever temporary cooling is needed or where a window A/C isn't an option
- Built-in condensate disposal
- 60" single hose for fast installation
- Automatic louver swing
- Washable filter is easily accessed
- 24-hour timer for better energy control

Square Feet to be Conditioned	Capacity Needed (BTUH)
100 - 150	8,000
150 - 250	
250 - 300	
300 - 350	10,000
350 - 400	
400 - 450	
450 - 550	12,000



COOL



DEHUMIDIFY



FAN



1 Garantie limitée de 1 an
Year Limited Warranty
Garantía limitada de un año

SOME LIMITATIONS APPLY.
SEE PRINTED WARRANTY FOR DETAILS.
Certains restrictions s'appliquent, voir garantie imprimée pour plus de détails.
Se aplican algunas limitaciones, consulte el documento impreso de la garantía para obtener detalles.