

# 14,000 BTU/H

## CB143



### Specifications

Cooling Capacity BTUH	14,000
Approx. Sq. Ft. Cooling	550-700
EER/CEER	9.3/9.5
Energy Star®	YES
Certifications	UL
Refrigerant	R410A
Power Supply	208/230/1/60
Humidity Removal Pts/Hr	2.96
Ventilation Control	NO
Fan Only	YES
Fan Speeds Cool/Fan	3
Air Delivery Max. CFM	296
dB Level (hi/med/low)	61/60/59
Amps Cooling	7.5
Maximum Fuse Size	15
Power Cord	6-15P
Remote Control	YES
Slide-Out Chassis	NO
Interior Trim Kit	YES
Max Wall Thickness	12
Shipping Weight (lbs.)	89
Height (in.)	14.5
Width (in.)	24.2
Depth (in.)	20.3

## ROOM AIR CONDITIONER



**Guide des tailles d'ouverture de mur**  
**Guide to Wall Opening Sizes**  
 Guía de tamaños de apertura de pared

Vérifiez la taille de l'ouverture de votre mur. L'ouverture devrait tomber dans la plage indiquée sur le diagramme.


Verify the size of your wall opening. The opening should fall in the range shown in the diagram.

Verifique el tamaño de la abertura de su pared. La abertura deberá estar dentro de los límites que se muestran en el diagrama.

To be used with sleeve EA448F

### Electrical Requirements

Exigences électriques



**15A-230V**  
**NEMA 6-15P**

### Features

- Electronic controls
- Wireless remote
- Auto Restart in the event of power failure
- Energy Saver mode; fan cycles with cooling
- Slide out washable filter
- 3 fan speeds
- Decibel ratings: 59.2, 60.1, 61.3
- Designed to fit most TTW sleeves

### Selection Guide - Guide de sélection

Area to be Cooled - Zone à refroidir		
Square Feet to be conditioned pieds carrés	Square Meters to be conditioned mètres carrés	Capacity Needed (BTUH) Capacité nécessaire
100 - 150	9.3 - 13.9	5,000
150 - 250	13.9 - 23.2	6,000
250 - 300	23.2 - 27.9	7,000
300 - 350	27.9 - 32.5	8,000
350 - 400	32.5 - 37.2	9,000
400 - 450	37.2 - 41.8	10,000
450 - 550	41.8 - 51.1	12,000
550 - 700	51.1 - 65.1	14,000
550 - 700	51.1 - 65.1	15,000
700 - 1,000	65.1 - 92.9	18,000
1,000 - 1,200	92.9 - 111.5	21,000
1,200 - 1,400	111.5 - 130.1	23,000
1,400 - 1,500	130.1 - 139.4	24,000
1,500 - 2,000	139.4 - 185.8	30,000
2,000 - 2,500	185.8 - 232.3	34,000

**Heavily shaded room - reduce capacity by 10%**  
 Chambre très ombragée - une capacité réduite de 10%  
 Sala muy sombreada - reducir la capacidad en un 10%

**Very sunny room - increase capacity by 10%**  
 Chambre très ensoleillée - Augmentation de la capacité de 10%  
 Habitación muy soleada - aumentar la capacidad en un 10%

**Use in kitchen - increase capacity by 4,000 BTUs**  
 Utiliser dans la cuisine - Augmentation de la capacité de 4,000 BTUs  
 Uso en la cocina: aumente la capacidad en 4,000 BTU

**More than two people regularly use the room - add 600 BTUs for each additional person**  
 Plus de deux personnes utilisent régulièrement la salle - Ajouter 600 BTUs pour chaque personne supplémentaire  
 Más de dos personas usan la sala con regularidad: agregue 600 BTU por cada persona adicional

**To calculate square footage - multiply WIDTH x LENGTH**  
 Pour calculer la superficie en pieds carrés, multipliez la - largeur par la longueur  
 Para calcular pies cuadrados, multiplique ANCHO x LONGITUD

**Special Features**  
 Caractéristiques spéciales  
 Funciones especiales

**Energy Saver Mode**  
 Mode économie d'énergie  
 Modo ahorrador de energía

**Sleep Mode**  
 Mode "veille"  
 Modo suspendido

**Check Filter Indicator**  
 L'indicateur de filtre  
 Indicador de inspección de filtro

Specifications from www.energyguide.gov  
 Especificaciones de www.energyguide.gov



MULTI-DIRECTIONAL



COOLING



**1** Garantie limitée de 1 an  
 Year Limited Warranty  
 Garantía limitada de un año

SOME LIMITATIONS APPLY.  
 SEE PRINTED WARRANTY FOR DETAILS.  
 Certaines restrictions s'appliquent, voir garantie imprimée pour plus de détails.  
 Se aplican algunas limitaciones, consulte el documento impreso de la garantía para obtener detalles