

10,000 BTU/H

CEP-101



Specifications

Cooling Capacity BTUH	10,000
Approx. Sq. Ft. Cooling	400-450
EER	8.9
SACC BTUH	5,800
Energy Star®	NO
Certifications	UL
Refrigerant	R32
Power Supply	115V 60Hz
Humidity Removal Pts/Hr	4.44
Ventilation Control	NO
Fan Only	Yes
Fan Speeds Cool/Fan	3/3
Air Delivery Max. CFM	218
dB Level (hi/med/low)	54.5
Amps Cooling	10
Maximum Fuse Size	15
Power Cord	5-15P
Window Mounting Kit	YES
Remote Control	YES
Slide-Out Chassis	NO
Interior Trim Kit	NO
Minimum Window Opening (in.)	12
Shipping Weight (lbs.)	65.3
Height (in.)	28.3
Width (in.)	17.1
Depth (in.)	13.5

PORTABLE AIR CONDITIONER



Features

- Cool a room without any special wiring, and move the unit from room to room as needed
- Ideal wherever temporary cooling is needed or where a window A/C isn't an option
- Built-in condensate disposal
- 60" single hose for fast installation
- Automatic louver swing
- Washable filter is easily accessed
- 24-hour timer for better energy control



Square Feet to be Conditioned	Capacity Needed (BTUH)
100 - 150	8,000
150 - 250	
250 - 300	
300 - 350	10,000
350 - 400	
400 - 450	
450 - 550	12,000



COOL



DEHUMIDIFY



FAN

1 Garantie limitée de 1 an
Year Limited Warranty
 Garantía limitada de un año

SOME LIMITATIONS APPLY.
 SEE PRINTED WARRANTY FOR DETAILS.
 Certaines restrictions s'appliquent, voir garantie imprimée pour plus de détails.
 Se aplican algunas limitaciones, consulte el documento impreso de la garantía para obtener detalles.