

25,000 BTU/H

CEW243



Specifications

Cooling Capacity BTUH	25,000
Approx. Sq. Ft. Cooling	1,400-1,500
EER	10.3
Energy Star®	YES
Certifications	UL
Refrigerant	R32
Power Supply	208/230/1/60
Humidity Removal Pts/Hr	5.71
Ventilation Control	YES
Fan Only	YES
Fan Speeds Cool/Fan	3
Air Delivery Max. CFM	523
dB Level (hi/med/low)	63/62/61
Amps Cooling	10.8/11.8
Maximum Fuse Size	20
Power Cord	6-20P
Window Mounting Kit	YES
Remote Control	YES
Slide-Out Chassis	YES
Interior Trim Kit	NO
Max Wall Thickness	11
Minimum Window Opening (in.)	29
Shipping Weight (lbs.)	151.5
Height (in.)	18.6
Width (in.)	26.5
Depth (in.)	26.5

ROOM AIR CONDITIONER



Measure Area of the Room
Mesurer la surface de la pièce

CALCULATE ROOM SIZE
Calculer le tamaño de la habitación

Guide to Window Opening Size
Guide des tailles d'ouverture de fenêtre

Verify the size of your window opening.
The opening should fall in the range shown in the diagram.
Verifiez la taille de votre ouverture de fenêtre.
L'ouverture devrait tomber dans la plage indiquée sur le diagramme.

Electrical Requirements
Exigences électriques

20A-230V
NEMA 6-20P

Features

- Electronic controls
- Wireless remote
- Auto Restart in the event of a power failure
- Ventilation control to keep air fresh
- Energy Saver mode; Fan cycles with cooling
- 3 fan speeds
- Window mounting kit included
- Slide out washable filter
- Decibal rating a pleasant 52.3 on low speed

Selection Guide - Guide de sélection

Area to be Cooled - Zone à refroidir		Capacity Needed (BTUH) <i>Capacité nécessaire</i>
Square Feet to be conditioned <i>piés carrés</i>	Square Meters to be conditioned <i>mètres carrés</i>	
100 - 150	9.3 - 13.9	5,000
150 - 250	13.9 - 23.2	6,000
250 - 300	23.2 - 27.9	7,000
300 - 350	27.9 - 32.5	8,000
350 - 400	32.5 - 37.2	9,000
400 - 450	37.2 - 41.8	10,000
450 - 550	41.8 - 51.1	12,000
550 - 700	51.1 - 65.1	14,000
550 - 700	51.1 - 65.1	15,000
700 - 1,000	65.1 - 92.9	18,000
1,000 - 1,200	92.9 - 111.5	21,000
1,200 - 1,400	111.5 - 130.1	23,000
1,400 - 1,500	130.1 - 139.4	25,000
1,500 - 2,000	139.4 - 185.8	30,000
2,000 - 2,500	185.8 - 232.3	34,000

Heavily shaded room - reduce capacity by 10%
Chambre très ombragée - une capacité réduite de 10%
Sala muy sombreada - reducir la capacidad en un 10%

Very sunny room - increase capacity by 10%
Chambre très ensoleillée - augmentation de la capacité de 10%
Habitación muy soleada - aumentar la capacidad en un 10%

Use in kitchen - increase capacity by 4,000 BTUs
Utiliser dans la cuisine - Augmentation de la capacité de 4,000 BTUs
Uso en la cocina: aumente la capacidad en 4,000 BTU

More than two people regularly use the room - add 600 BTUs for each additional person
Plus de deux personnes utilisent régulièrement la salle - Ajouter 600 BTUs pour chaque personne supplémentaire
Más de dos personas usan la sala con regularidad: agregue 600 BTU por cada persona adicional

To calculate square footage - multiply WIDTH x LENGTH
Pour calculer la superficie en piés carrés, multipliez la - largeur par la longueur
Para calcular piés cuadrados, multiplique ANCHO x LONGITUD

Special Features
Caractéristiques spéciales
Funciones especiales

Energy Saver Mode
Mode économie d'énergie
Modo ahorrador de energía

Sleep Mode
Mode "veille"
Modo suspendido

Check Filter Indicator
L'indicateur de filtre
Indicador de inspección de filtro

Specifications from www.energystar.gov
Especificaciones de www.energystar.gov



MULTI-DIRECTIONAL



COOLING



UL

1 Garantie limitée de 1 an
Year Limited Warranty
Garantía limitada de un año

SOME LIMITATIONS APPLY.
SEE PRINTED WARRANTY FOR DETAILS.
Certaines restrictions s'appliquent, voir garantie imprimée pour plus de détails.
Se aplican algunas limitaciones, consulte el documento impreso de la garantía para obtener detalles.