

Window Air Conditioner

5,000 BTUH

CMW051B



Specifications

Cooling Capacity BTUH	5,000
Approx. Sq. Ft. Cooling	100-150
EER	11.1
Heating Capacity BTUH (electric)	DNA
Power Supply	115/60/1
Humidity Removal Pts/Hr	1.27
Ventilation Control	NO
Fan Only	YES
Fan Speeds Cool/Fan	3
Air Delivery Max. CFM	241
dB Level (hi/med/low)	56.3/53
Amps Cooling	4.0
Amps Heating	DNA
Maximum Fuse Size	15
Power Cord	5-15P
Window Mounting Kit	YES
Remote Control	NO
Max Wall Thickness	3.3"
Shipping Weight (lbs.)	42
Dimensions (in.)	Height 12.1
	Width 16
	Depth 15.4



Features

- Convenient dual dial control
- Slide out washable filter
- 3 fan speeds
- Window mounting kit included
- Compact cabinet
- Non-Energy Star

1 Year Limited Warranty



6,000 BTUH

CEW061BS



Specifications

Cooling Capacity BTUH	6,000
Approx. Sq. Ft. Cooling	150-250
EER	12.2
Heating Capacity BTUH (electric)	DNA
Power Supply	115/60/1
Humidity Removal Pts/Hr	1.48
Ventilation Control	NO
Fan Only	YES
Fan Speeds Cool/Fan	3
Air Delivery Max. CFM	259
dB Level (hi/med/low)	55.5/54.1/51.9
Amps Cooling	4.5
Amps Heating	DNA
Maximum Fuse Size	15
Power Cord	5-15P
Window Mounting Kit	YES
Remote Control	YES
Max Wall Thickness	5"
Shipping Weight (lbs.)	52
Dimensions (in.)	Height 13.4
	Width 18.5
	Depth 15.7



Features

- Electronic controls
- Wireless remote
- Auto Restart in the event of a power failure
- Energy Saver mode; fan cycles with cooling
- 24-hour timer for better energy control
- Window mounting kit included
- Slide out washable filter
- Decibal rating a pleasant 53.7 on low speed

1 Year Limited Warranty

8,000 BTUH

CEW081BS



Specifications

Cooling Capacity BTUH	8,000
Approx. Sq. Ft. Cooling	300-350
EER	12
Heating Capacity BTUH (electric)	DNA
Power Supply	115/60/1
Humidity Removal Pts/Hr	2.11
Ventilation Control	no
Fan Only	YES
Fan Speeds Cool/Fan	3
Air Delivery Max. CFM	230.3
dB Level (hi/med/low)	58.4/55.8/53.7
Amps Cooling	5.9
Amps Heating	DNA
Maximum Fuse Size	15
Power Cord	5-15P
Window Mounting Kit	YES
Remote Control	YES
Max Wall Thickness	5.7"
Shipping Weight (lbs.)	55.8
Dimensions (in.)	Height 13.4
	Width 18.5
	Depth 17.5



Features

- Electronic controls
- Wireless remote
- Auto Restart in the event of a power failure
- Energy Saver mode; fan cycles with cooling
- 24-hour timer for better energy control
- Window mounting kit included
- Slide out washable filter
- Decibal rating a pleasant 53.7 on low speed

Window Air Conditioner

10,000 BTUH

CEW101BS



Specifications

Cooling Capacity BTUH	10,000
Approx. Sq. Ft. Cooling	400-450
EER	12
Heating Capacity BTUH (electric)	DNA
Power Supply	115/60/1
Humidity Removal Pts/Hr	2.32
Ventilation Control	YES
Fan Only	YES
Fan Speeds Cool/Fan	3
Air Delivery Max. CFM	285
dB Level (hi/med/low)	59.5/58.3/57
Amps Cooling	5.9
Amps Heating	DNA
Maximum Fuse Size	15
Power Cord	5-15P
Window Mounting Kit	YES
Remote Control	YES
Max Wall Thickness	7.3"
Shipping Weight (lbs.)	79.4
Dimensions (in.)	Height 14.6
	Width 19
	Depth 21.5



Features

- Electronic controls
- Wireless remote
- Auto Restart in the event of a power failure
- Ventilation control to keep air fresh
- Energy Saver mode; fan cycles with cooling
- 3 fan speeds
- Window mounting kit included
- Slide out washable filter
- Decibal rating a pleasant 57.7 on low speed

12,000 BTUH

CEW121BS



Specifications

Cooling Capacity BTUH	12,000
Approx. Sq. Ft. Cooling	450-550
EER	12
Heating Capacity BTUH (electric)	DNA
Power Supply	115/60/1
Humidity Removal Pts/Hr	2.54
Ventilation Control	YES
Fan Only	YES
Fan Speeds Cool/Fan	3
Air Delivery Max. CFM	300
dB Level (hi/med/low)	60.5/59.3/57.7
Amps Cooling	8.7
Amps Heating	DNA
Maximum Fuse Size	15
Power Cord	5-15P
Window Mounting Kit	YES
Remote Control	YES
Max Wall Thickness	7.3"
Shipping Weight (lbs.)	78.7
Dimensions (in.)	Height 14.6
	Width 19
	Depth 21.5



Features

- Electronic controls
- Wireless remote
- Auto Restart in the event of a power failure
- Ventilation control to keep air fresh
- Energy Saver mode; fan cycles with cooling
- 3 fan speeds
- Window mounting kit included
- Slide out washable filter
- Decibal rating a pleasant 53.7 on low speed

15,000 BTUH

CEW151BS



Specifications

Cooling Capacity BTUH	15,100
Approx. Sq. Ft. Cooling	550-700
EER	11.8
Heating Capacity BTUH (electric)	DNA
Power Supply	115/60/1
Humidity Removal Pts/Hr	3.17
Ventilation Control	YES
Fan Only	YES
Fan Speeds Cool/Fan	3
Air Delivery Max. CFM	353
dB Level (hi/med/low)	56.4/53.7/52.5
Amps Cooling	11.5
Amps Heating	DNA
Maximum Fuse Size	15
Power Cord	5-15P
Window Mounting Kit	YES
Remote Control	YES
Max Wall Thickness	8"
Shipping Weight (lbs.)	117.9
Dimensions (in.)	Height 17.9
	Width 23.6
	Depth 25.4



Features

- Electronic controls
- Wireless remote
- Auto Restart in the event of a power failure
- Ventilation control to keep air fresh
- Energy Saver mode; fan cycles with cooling
- 3 fan speeds
- Window mounting kit included
- Slide out washable filter
- Decibal rating a pleasant 52.5 on low speed



COOLING



MULTI-DIRECTIONAL



REMOTE

Window Air Conditioner

18,000 BTUH

CEW183AS



Specifications

Cooling Capacity BTUH	18,000
Approx. Sq. Ft. Cooling	700-1,000
EER	11.8
Heating Capacity BTUH (electric)	DNA
Power Supply	208/230/1/60
Humidity Removal Pts/Hr	3.8
Ventilation Control	YES
Fan Only	YES
Fan Speeds Cool/Fan	3
Air Delivery Max. CFM	430
dB Level (hi/med/low)	60/57/54
Amps Cooling	7/7.5
Amps Heating	DNA
Maximum Fuse Size	15
Power Cord	6-15P
Window Mounting Kit	YES
Remote Control	YES
Max Wall Thickness	11"
Shipping Weight (lbs.)	129
Dimensions (in.)	
Height	17.9
Width	23.6
Depth	25.4



Features

- Electronic controls
- Wireless remote
- Auto Restart in the event of a power failure
- Ventilation control to keep air fresh
- Energy Saver mode; Fan cycles with cooling
- 3 fan speeds
- Window mounting kit included
- Slide out washable filter
- Decibal rating a pleasant 56 on low speed

1 Year Limited Warranty

24,000 BTUH

CEW243AS



Specifications

Cooling Capacity BTUH	24,000
Approx. Sq. Ft. Cooling	1,400-1,500
EER	10.3
Heating Capacity BTUH (electric)	DNA
Power Supply	208/230/1/60
Humidity Removal Pts/Hr	5.71
Ventilation Control	YES
Fan Only	YES
Fan Speeds Cool/Fan	3
Air Delivery Max. CFM	447
dB Level (hi/med/low)	56, 59, 61
Amps Cooling	10.8/11.8
Amps Heating	DNA
Maximum Fuse Size	20
Power Cord	6-20P
Window Mounting Kit	YES
Remote Control	YES
Max Wall Thickness	11"
Shipping Weight (lbs.)	151.5
Dimensions (in.)	
Height	18.6
Width	26.5
Depth	26.5



Features

- Electronic controls
- Wireless remote
- Auto Restart in the event of a power failure
- Ventilation control to keep air fresh
- Energy Saver mode; Fan cycles with cooling
- 3 fan speeds
- Window mounting kit included
- Slide out washable filter
- Decibal rating a pleasant 52.3 on low speed



COOLING



MULTI-DIRECTIONAL



REMOTE