

Portable Air Conditioner

8,000 BTUH CEP-081A



Specifications

Cooling Capacity BTUH	8,000
Approx. Sq. Ft. Cooling	300-350
EER	8.9
Refrigerant	R-410A
Power Supply	115V 60Hz
Humidity Removal Pts./Hr.	3.38
Fan Only	Yes
Fan Speeds Cool/Fan	1/1
Air Delivery Max. CFM	176
Amps Cooling	8.0
dB Level (hi/low)	55
Maximum Fuse Size	15A
Power Cord	15A Parallel NEMA 5-15P
Window Mounting Kit	Yes
Remote Control	Yes
Shipping Weight (lbs.)	67.1
Dimensions (in.)	Height 28.3
	Width 17.1
	Depth 13



10,000 BTUH CEP-101A



Specifications

Cooling Capacity BTUH	10,000
Approx. Sq. Ft. Cooling	400-450
EER	8.9
Refrigerant	R-410A
Power Supply	115V 60Hz
Humidity Removal Pts./Hr.	4.44
Fan Only	Yes
Fan Speeds Cool/Fan	1/1
Air Delivery Max. CFM	176
Amps Cooling	10
dB Level (hi/low)	55
Maximum Fuse Size	15A
Power Cord	15A Parallel NEMA 5-15P
Window Mounting Kit	Yes
Remote Control	Yes
Shipping Weight (lbs.)	67.1
Dimensions (in.)	Height 28.3
	Width 17.1
	Depth 13




12,000 BTUH CEP-121A



Specifications

Cooling Capacity BTUH	12,000
Approx. Sq. Ft. Cooling	450-550
EER	8.9
Refrigerant	R-410A
Power Supply	115V 60Hz
Humidity Removal Pts./Hr.	5.28
Fan Only	Yes
Fan Speeds Cool/Fan	1/1
Air Delivery Max. CFM	206
Amps Cooling	12
dB Level (hi/low)	56
Maximum Fuse Size	15A
Power Cord	15A Parallel NEMA 5-15P
Window Mounting Kit	Yes
Remote Control	Yes
Shipping Weight (lbs.)	72.6
Dimensions (in.)	Height 28.3
	Width 17.1
	Depth 13



Square Feet to be conditioned	Capacity Needed (BTUH)
100 - 150	8,000
150 - 250	
250 - 300	
300 - 350	
350 - 400	10,000
400 - 450	
450 - 550	12,000

Features

- Cool a room without any special wiring, and move the unit from room to room as needed
- Ideal wherever temporary cooling is needed or where a window A/C isn't an option
- Built-in condensate disposal
- 48" single hose for fast installation
- Automatic louver swing
- Washable filter is easily accessed
- 24-hour timer for better energy control

1 Year Limited Warranty

