

12,000 BTU/H

CEPH-121C



Specifications

| | |
|--------------------------|-------------------------|
| Cooling Capacity BTUH | 12,000 |
| SACC BTUH | 6,000 |
| Approx. Sq. Ft. Cooling | 400-450 |
| EER | 9.6 |
| Heating Capacity BTUH | 10,000 |
| COP | 2.55 |
| Power Supply | 115V 60Hz |
| Humidity Removal Pts/Hr. | 5.49 |
| Fan Only | YES |
| Fan Speeds Cool/Heat/Fan | 3 |
| Air Delivery Max. CFM | 333 |
| Amps Cooling | 10.6 |
| Amps Heating | 10.3 |
| dB Level (hi/low) | 53/52/51 |
| Maximum Fuse Size | 15A |
| Power Cord | 15A Parallel NEMA 5-15P |
| Window Mounting Kit | Yes |
| Remote Control | Yes |
| Shipping Weight (lbs.) | 70.5 |
| Dimensions (in.) | H 28.15 |
| | W 17.61 |
| | D 14.56 |

Features

- Cool and heat a room without any special wiring, and move the unit from room to room as needed
- Ideal wherever temporary cooling is needed or where a window A/C isn't an option
- Built-in condensate disposal
- 60" single hose for fast installation
- Automatic louver swing
- Washable filter is easily accessed
- 24-hour timer for better energy control

PORTABLE AIR CONDITIONER



| Square Feet to be Conditioned | Capacity Needed (BTUH) |
|-------------------------------|------------------------|
| 100 - 150 | 8,000 |
| 150 - 250 | |
| 250 - 300 | |
| 300 - 350 | 10,000 |
| 350 - 400 | |
| 400 - 450 | |
| 450 - 550 | 12,000 |



HEAT



COOL



DEHUMIDIFY



FAN



1 Garantie limitée de 1 an
Year Limited Warranty
Garantía limitada de un año

SOME LIMITATIONS APPLY.
SEE PRINTED WARRANTY FOR DETAILS.
Certains restrictions s'appliquent, voir garantie imprimée pour plus de détails.
Se aplican algunas limitaciones, consulte el documento impreso de la garantía para obtener detalles.