

5,000 BTU/H

CMW051



Specifications

Cooling Capacity BTUH	5,000
Approx. Sq. Ft. Cooling	100-150
EER	11.1
Energy Star®	NO
Certifications	CSA
Refrigerant	R32
Power Supply	115/60/1
Humidity Removal Pts/Hr	1.27
Ventilation Control	NO
Fan Only	YES
Fan Speeds Cool/Fan	3
Air Delivery Max. CFM	145
dB Level (hi/med/low)	56/52
Amps Cooling	4.6
Maximum Fuse Size	15
Power Cord	5-15P
Window Mounting Kit	YES
Remote Control	NO
Slide-Out Chassis	NO
Interior Trim Kit	NO
Max Wall Thickness	3.3"
Minimum Window Opening (in.)	18
Shipping Weight (lbs.)	42
Height (in.)	12.1
Width (in.)	16
Depth (in.)	13.9

Features

- Convenient dual dial control
- Slide out washable filter
- 3 fan speeds
- Window mounting kit included
- Compact cabinet

ROOM AIR CONDITIONER



Measure Area of the Room
Mesurer la surface de la pièce

CALCULATE ROOM SIZE
Calculer le tamaño de la habitación

Guide to Window Opening Size
Guide des tailles d'ouverture de fenêtre

Verify the size of your window opening. The opening should fall in the range shown in the diagram.
Vérifier la taille de votre ouverture de fenêtre. L'ouverture devrait tomber dans la plage indiquée sur le diagramme.

Electrical Requirements
Exigences électriques

15A-115V
NEMA 5-15P

Selection Guide - Guide de sélection

Area to be Cooled - Zone à refroidir		Capacity Needed (BTUH) Capacité nécessaire
Square Feet to be conditioned pieds carrés	Square Meters to be conditioned mètres carrés	
100 - 150	9.3 - 13.9	5,000
150 - 250	13.9 - 23.2	6,000
250 - 300	23.2 - 27.9	7,000
300 - 350	27.9 - 32.5	8,000
350 - 400	32.5 - 37.2	9,000
400 - 450	37.2 - 41.8	10,000
450 - 550	41.8 - 51.1	12,000
550 - 700	51.1 - 65.1	14,000
550 - 700	51.1 - 65.1	15,000
700 - 1,000	65.1 - 92.9	18,000
1,000 - 1,200	92.9 - 111.5	21,000
1,200 - 1,400	111.5 - 130.1	23,000
1,400 - 1,500	130.1 - 139.4	24,000
1,500 - 2,000	139.4 - 185.8	30,000
2,000 - 2,500	185.8 - 232.3	34,000

Specifications from www.energystar.gov
Spécifications de www.energystar.gov

Heavily shaded room - reduce capacity by 10%
Chambre très ombragée - une capacité réduite de 10%
Sala muy sombreada - reducir la capacidad en un 10%

Very sunny room - increase capacity by 10%
Chambre très ensoleillée - Augmentation de la capacité de 10%
Habitación muy soleada - aumentar la capacidad en un 10%

Use in kitchen - increase capacity by 4,000 BTUs
Utiliser dans la cuisine - Augmentation de la capacité de 4,000 BTUs
Uso en la cocina: aumente la capacidad en 4,000 BTU

More than two people regularly use the room - add 600 BTUs for each additional person
Plus de deux personnes utilisent régulièrement la salle - Ajouter 600 BTUs pour chaque personne supplémentaire
Más de dos personas usan la sala con regularidad: agregue 600 BTU por cada persona adicional

To calculate square footage - multiply WIDTH x LENGTH
Pour calculer la superficie en pieds carrés, multiplier la - largeur par la longueur
Para calcular pies cuadrados, multiplique ANCHO x LONGITUD



MULTI-DIRECTIONAL



COOLING



CSA US

1 Garantie limitée de 1 an
Year Limited Warranty
Garantía limitada de un año

SOME LIMITATIONS APPLY.
SEE PRINTED WARRANTY FOR DETAILS.
Certaines restrictions s'appliquent, voir garantie imprimée pour plus de détails.
Se aplican algunas limitaciones, consulte el documento impreso de la garantía para obtener detalles.