# 5,000 BTUH

## **CMW051B**



### **Specifications**

Cooling Capacity BTUH	5,000	
Approx. Sq. Ft. Cooling	100-150	
EER	11.1	
Heating Capacity BTUH (electric)	DNA	
Power Supply	115/60/1	
Humidity Removal Pts/Hr	1.27	
Ventilation Control	NO	
Fan Only	YES	
Fan Speeds Cool/Fan	3	
Air Delivery Max. CFM	145	
dB Level (hi/med/low)	56/52	
Amps Cooling	4.6	
Amps Heating	DNA	
Maximum Fuse Size	15	
Power Cord	5-15P	
Window Mounting Kit	YES	
Remote Control	NO	
Max Wall Thickness	3.3"	
Shipping Weight (lbs.)	42	
Dimensions (in.) Height	12.1	
Width	16	
Depth	13.9	



## **Features**

- Convenient dual dial control
- Slide out washable filter
- 3 fan speeds
- Window mounting kit included
- Compact cabinet
- Non-Energy Star

# 5,000 BTUH

# **CMW051C**



## **Specifications**

Cooling Capacity BTUH	5,000	
Approx. Sq. Ft. Cooling	100-150	
EER	11	
Heating Capacity BTUH (electric)	DNA	
Power Supply	115/60/1	
Humidity Removal Pts/Hr	1.27	
Ventilation Control	NO	
Fan Only	YES	
Fan Speeds Cool/Fan	2	
Air Delivery Max. CFM	141	
dB Level (hi/med/low)	54/50	
Amps Cooling	3.9	
Amps Heating	DNA	
Maximum Fuse Size	15	
Power Cord	5-15P	
Window Mounting Kit	YES	
Remote Control	NO	
Max Wall Thickness	5"	
Shipping Weight (lbs.)	41.89	
Dimensions (in.) Height	15.82	
Width	18.15	
Depth	16.85	





### **Features**

- Convenient dual dial control
- Slide out washable filter
- 3 fan speeds
- Window mounting kit included
- Compact cabinet
- Non-Energy Star

# 6,000 BTUH

## CEW061BS



## Specifications

Cooling Capacity BTUH	6,000	
Approx. Sq. Ft. Cooling	150-250	
EER	12.2	
Heating Capacity BTUH (electric)	DNA	
Power Supply	115/60/1	
Humidity Removal Pts/Hr	1.48	
Ventilation Control	NO	
Fan Only	YES	
Fan Speeds Cool/Fan	3	
Air Delivery Max. CFM	259	
dB Level (hi/med/low)	55.5/54.1/51.9	
Amps Cooling	4.5	
Amps Heating	DNA	
Maximum Fuse Size	15	
Power Cord	5-15P	
Window Mounting Kit	YES	
Remote Control	YES	
Max Wall Thickness	5"	
Shipping Weight (lbs.)	52	
Dimensions (in.) Height	13.4	
Width	18.5	
Depth	15.7	







- Electronic controls
- Wireless remote
- Auto Restart in the event of a power failure
- Energy Saver mode; fan cycles with
- 24-hour timer for better energy control
- Window mounting kit included
- Slide out washable filter
- Decibal rating a pleasant 51.9 on low speed







# 6,000 BTUH

## CEW061CS



## Specifications

<u> </u>		
Cooling Capacity BTUH	6,000	
Approx. Sq. Ft. Cooling	150-250	
EER	12.2	
Heating Capacity BTUH (electric)	DNA	
Power Supply	115/60/1	
Humidity Removal Pts/Hr	1.48	
Ventilation Control	NO	
Fan Only	YES	
Fan Speeds Cool/Fan	3	
Air Delivery Max. CFM	141	
dB Level (hi/med/low)	55.5/54.1/51.9	
Amps Cooling	4.5	
Amps Heating	DNA	
Maximum Fuse Size	15	
Power Cord	5-15P	
Window Mounting Kit	YES	
Remote Control	YES	
Max Wall Thickness	5"	
Shipping Weight (lbs.)	47.4	
Dimensions (in.) Height	15.82	
Width	18.15	
Depth	16.85	
Dop	10100	







#### **Features**

- Electronic controls
- Wireless remote
- Auto Restart in the event of a power failure
- Energy Saver mode; fan cycles with cooling
- 24-hour timer for better energy control
- Window mounting kit included
- Slide out washable filter
- Decibal rating a pleasant 51.9 on low speed

# 8,000 BTUH

## **CEW081BS**



### **Specifications**

Cooling Capacity BTUH	8,000	
Approx. Sq. Ft. Cooling	300-350	
EER	12	
Heating Capacity BTUH (electric)	DNA	
Power Supply	115/60/1	
Humidity Removal Pts/Hr	2.11	
Ventilation Control	NO	
Fan Only	YES	
Fan Speeds Cool/Fan	3	
Air Delivery Max. CFM	230.3	
dB Level (hi/med/low)	58.4/55.8/53.7	
Amps Cooling	5.9	
Amps Heating	DNA	
Maximum Fuse Size	15	
Power Cord	5-15P	
Window Mounting Kit	YES	
Remote Control	YES	
Max Wall Thickness	5.7"	
Shipping Weight (lbs.)	55.8	
Dimensions (in.) Height	13.4	
Width	18.5	
Depth	17.5	







### **Features**

- Electronic controls
- Wireless remote
- Auto Restart in the event of a power failure
- Energy Saver mode; fan cycles with cooling
- 24-hour timer for better energy control
- Window mounting kit included
- Slide out washable filter
- Decibal rating a pleasant 53.7 on low speed

# 8,000 BTUH

### CEW081CS



### **Specifications**

Cooling Capacity BTUH	8,000	
Approx. Sq. Ft. Cooling	300-350	
EER	12.1	
Heating Capacity BTUH (electric)	DNA	
Power Supply	115/60/1	
Humidity Removal Pts/Hr	2.11	
Ventilation Control	NO	
Fan Only	YES	
Fan Speeds Cool/Fan	3	
Air Delivery Max. CFM	141	
dB Level (hi/med/low)	58.4/55.8/53.7	
Amps Cooling	6.1	
Amps Heating	DNA	
Maximum Fuse Size	15	
Power Cord	5-15P	
Window Mounting Kit	YES	
Remote Control	YES	
Max Wall Thickness	5"	
Shipping Weight (lbs.)	52.91	
Dimensions (in.) Height	15.82	
Width	21.41	
Depth	17.63	



- Electronic controls
- Wireless remote
- Auto Restart in the event of a power failure
- Energy Saver mode; fan cycles with cooling
- 24-hour timer for better energy control
- Window mounting kit included
- Slide out washable filter
- Decibal rating a pleasant 53.7 on low speed







# 10,000 BTUH

## **CEW101BS**



### **Specifications**

=		
Cooling Capacity BTUH	10,000	
Approx. Sq. Ft. Cooling	400-450	
EER	12	
Heating Capacity BTUH (electric)	DNA	
Power Supply	115/60/1	
Humidity Removal Pts/Hr	2.32	
Ventilation Control	YES	
Fan Only	YES	
Fan Speeds Cool/Fan	3	
Air Delivery Max. CFM	285	
dB Level (hi/med/low)	59.5/58.3/57	
Amps Cooling	7.5	
Amps Heating	DNA	
Maximum Fuse Size	15	
Power Cord	5-15P	
Window Mounting Kit	YES	
Remote Control	YES	
Max Wall Thickness	7.3"	
Shipping Weight (lbs.)	68.8	
Dimensions (in.) Height	14.6	
Width	19	
Depth	21.5	







### **Features**

- Electronic controls
- Wireless remote
- Auto Restart in the event of a power failure
- Ventilation control to keep air fresh
- Energy Saver mode; fan cycles with cooling
- 3 fan speeds
- Window mounting kit included
- Slide out washable filter
- Decibal rating a pleasant 57 on low speed

# 12,000 BTUH

## **CEW121BS**



### **Specifications**

Cooling Capacity BTUH	12,000
Approx. Sq. Ft. Cooling	450-550
EER	12
Heating Capacity BTUH (electric)	DNA
Power Supply	115/60/1
Humidity Removal Pts/Hr	2.54
Ventilation Control	YES
Fan Only	YES
Fan Speeds Cool/Fan	3
Air Delivery Max. CFM	300
dB Level (hi/med/low)	60.5/59.3/57.7
Amps Cooling	8.7
Amps Heating	DNA
Maximum Fuse Size	15
Power Cord	5-15P
Window Mounting Kit	YES
Remote Control	YES
Max Wall Thickness	7.3"
Shipping Weight (lbs.)	78.7
Dimensions (in.) Height	14.6
Width	19
Depth	21.5







### **Features**

- Electronic controls
- Wireless remote
- Auto Restart in the event of a power failure
- Ventilation control to keep air fresh
- Energy Saver mode; fan cycles with cooling
- 3 fan speeds
- Window mounting kit included
- Slide out washable filter
- Decibal rating a pleasant 57.7 on low speed

# 15,000 BTUH

### CEW151BS



### **Specifications**

Cooling Capacity BTUH	15,100	
Approx. Sq. Ft. Cooling	550-700	
EER	11.8	
Heating Capacity BTUH (electric)	DNA	
Power Supply	115/60/1	
Humidity Removal Pts/Hr	3.17	
Ventilation Control	YES	
Fan Only	YES	
Fan Speeds Cool/Fan	3	
Air Delivery Max. CFM	353	
dB Level (hi/med/low)	56.4/53.7/52.5	
Amps Cooling	11.5	
Amps Heating	DNA	
Maximum Fuse Size	15	
Power Cord	5-15P	
Window Mounting Kit	YES	
Remote Control	YES	
Max Wall Thickness	8"	
Shipping Weight (lbs.)	117.9	
Dimensions (in.) Height	17.9	
Width	23.6	
Depth	25.4	







- Electronic controls
- Wireless remote
- Auto Restart in the event of a power failure
- Ventilation control to keep air fresh
- Energy Saver mode; fan cycles with cooling
- 3 fan speeds
- Window mounting kit included
- Slide out washable filter
- Decibal rating a pleasant 52.5 on low speed



# 18,000 BTUH

## **CEW183BS**



## **Specifications**

18,000/17,700	
700-1,000	
11.8	
DNA	
208/230/1/60	
3.8	
YES	
YES	
3	
360	
60/57/54	
7/7.5	
DNA	
15	
6-15P	
YES	
YES	
11"	
129	
17.9	
23.6	
25.4	







### **Features**

- Electronic controls
- Wireless remote
- Auto Restart in the event of a power failure
- Ventilation control to keep air fresh
- Energy Saver mode; Fan cycles with cooling
- 3 fan speeds
- Window mounting kit included
- Slide out washable filter
- Decibal rating a pleasant 56 on low speed

# 25,000 BTUH

### CEW243BS



## Specifications

Cooling Capacity BT	UH	25,000/24,700
Approx. Sq. Ft. Cooling		1,400-1,500
EER		10.3
Heating Capacity BTUH (electric)		DNA
Power Supply		208/230/1/60
Humidity Removal Pts/Hr		5.71
Ventilation Control		YES
Fan Only		YES
Fan Speeds Cool/Fan		3
Air Delivery Max. Cl	FM	523
dB Level (hi/med/low)		63/62/61
Amps Cooling		10.8/11.8
Amps Heating		DNA
Maximum Fuse Size	;	20
Power Cord		6-20P
Window Mounting Kit		YES
Remote Control		YES
Max Wall Thickness		11"
Shipping Weight (lb	s.)	151.5
Dimensions (in.)	Height	18.6
	Width	26.5
	Depth	26.5







- Electronic controls
- Wireless remote
- Auto Restart in the event of a power failure
- Ventilation control to keep air fresh
- Energy Saver mode; Fan cycles with cooling
- 3 fan speeds
- Window mounting kit included
- Slide out washable filter
- Decibal rating a pleasant 52.3 on low speed